kemvit PUHTAUS JONKA TUNNET

KW Puolikiiltävä

Floor protector

Applications/work methods

Purpose of use
Semi glossy / glossy floor for plastic, linoleum, stone, rubber, varnished parquet floors and worn PUR surfaces. Very good for patch waxing.

Properties
White, milky liquid
When dry, it leaves the floor semi-gloss. The product is an easy to apply, highly abrasion-resistant, easy-to-use floor wax. KW Puolikiiltävä is well resistant to hand soaps.
Almost odourless.

Contains
Water-based acrylic/styrene co-polymer

pH 8,5

Instructions for use
To be used as is, undiluted. Apply 1-2 thin layers of wax to a clean, dry floor surface. For particularly worn areas, a single coat can be applied first. Allow the wax coatings to dry for 20-30 minutes between applications.
Sufficient for 80-100 m²/L. The effectiveness is dependent on the porosity of the floor surface and the application equipment.

The surface is walk-dry after the last layer has dried for about 45 minutes. It is recommended to move furniture into the room the following day to avoid scratches.

Product code	**Sales batch**	**GTIN** (pcs)
185031	10 x 1 L	6420617274580
185035	3 x 5 L	6420617274573

Product environmental guideline
Packaging recycling instructions see on the product label. Instructions for disposal of contents see in the safety data sheet.

Storage
Store at room temperature. Protect from freezing.

Made in Finland

For professional use only

Product card 1/2023

Kemvit Oy | 68410 Alaveteli | +358 40 773 0086 | www.kemvit.fi | info@kemvit.fi